



**PRODUCT DATA SHEET**

August, 1999

**SANDPIPER EB2M PUMP  
(Aluminum Version)**

**GENERAL INFORMATION**

This is an air-powered double diaphragm pump designed for applications requiring low flowrates and moderate head pressures. Performance is the same as the stainless steel version, only the materials are different.

This pump must be supplied with an external source of compressed air to operate. It can run dry for extended periods of time without damage. The flowrate is varied by regulating the air supply.

**PERFORMANCE DATA**

â Minimum Air Pressure:	.....	20 psi
â Maximum Air Pressure:	.....	100 psi
â Minimum Shutoff Head:	.....	44 ft (19 psi) <sup>(1)</sup>
â Maximum Shutoff Head:	.....	230 ft (100 psi) <sup>(1)</sup>
â Maximum Suction Lift:	.....	22 ft <sup>(2)</sup>
® Minimum Flow:	.....	0 gpm
â Maximum Flow:	.....	135 gpm
â Maximum Temperature:	.....	212° F
â Maximum Solids Size:	.....	¼"
â Displacement:	.....	0.43 gals/stroke

**PHYSICAL SPECIFICATIONS**

â Suction Flange:	.....	2" NPT (female)
â Discharge Flange:	.....	2" NPT (female)
â Air Inlet Port:	.....	¾" NPT (female)
â Overall Height:	.....	2'-0"
â Overall Width:	.....	1'-1"
â Air Exhaust Port:	.....	¾" NPT (female)
â Overall Length:	.....	1'-7"
â Total Weight:	.....	79 lbs.

**MATERIAL SPECIFICATIONS**

â Manifold Elbow:	.....	Aluminum
â Outer Chamber:	.....	Aluminum
â Inner Chamber:	.....	Aluminum
â Outer Diaphragm Plate:	.....	Aluminum
â Inner Diaphragm Plate:	.....	Plated steel
â Intermediate Housing:	.....	Aluminum
â Diaphragm Rod:	.....	416 stainless steel
â Valve Seat:	.....	Teflon
â Hardware:	.....	Plated steel
â Diaphragm:	.....	Teflon over neoprene
â Ball Valve:	.....	Teflon
â Air Valve:	.....	Aluminum

**Notes:**

<sup>(1)</sup> Based on 1.0 specific gravity

<sup>(2)</sup> For suction lifts exceeding 10 feet, fill the chambers with liquid prior to priming

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BAKER PUMPS, EITHER EXPRESS OR IMPLIED.