



PRODUCT DATA SHEET

November, 2002

4" PA4C60 GORMAN-RUPP PUMP

GENERAL INFORMATION

This pump is fitted with a compressor / ejector priming system to create a vacuum on the inlet to the pump. This allows the pump to automatically prime and reprime.

PERFORMANCE DATA

➤ Minimum Speed:	- 1200 rpm
➤ Maximum Speed:	- 2200 rpm
➤ Minimum Shutoff Head:	- 106 feet (46 psi) ⁽¹⁾ @ 1200 rpm
➤ Maximum Shutoff Head:	- 360 feet (155 psi) ⁽¹⁾ @ 2200 rpm
➤ Maximum Suction Lift:	- 25 feet ⁽⁶⁾ (@ 700 gpm)
➤ Minimum Flow:	- 350 gpm @ 2200 RPM
➤ Maximum Flow:	- 1600 gpm @ 2200 RPM
➤ Maximum Casing Press:	- 211 psi
➤ Maximum Temperature:	- 160°F
➤ Maximum Solids Size:	- 3" spherical

PUMP SPECIFICATIONS

➤ Impeller:	- 13-½", six vanes
➤ Wear Ring Clearance:	- 0.010" – 0.020" (front)
➤ Bearing Lubrication:	- SAE No. 30 oil
➤ Vacuum System:	- Piston compressor, 20 cfm, with venturi eductor
➤ Mech. Seal Lubrication:	- SAE No. 30 oil
➤ Dead Head Pressure:	-
@ 1600 RPM:	40 psi
@ 1800 RPM:	82 psi
@ 2000 RPM:	128 psi

PHYSICAL SPECIFICATIONS

➤ Suction Size:	- 6" flanged
➤ Discharge Size:	- 4" flanged
➤ Total Weight:	- 4,195 lbs. ⁽²⁾
➤ Overall Height:	- 7'-11" (top of lifting bail)
➤ Overall Width:	- 6'-0"
➤ Overall Length:	- 11'-5" (trailer length)

MATERIAL SPECIFICATIONS

➤ Pump Casing:	- Gray Iron No. 30
➤ Shaft Sleeve:	- 17-4 PH stainless steel
➤ Wear Rings:	- Impeller – Gray Iron No. 30 Suct. Hd. – Bronze C83600
➤ Mechanical Seal Faces:	- Silicon carb. / Tungsten carb.
➤ Priming Chamber:	- Gray Iron No. 30
➤ Pump Shaft:	- Stress-proof stainless steel
➤ O-rings:	- Buna-N and viton
➤ Impeller:	- Gray Iron No. 30
➤ Check Valve Body	- Gray Iron No. 30
➤ Check Valve Flapper:	- Buna-N

ENGINE SPECIFICATIONS

➤ Engine Make/Model:	- John Deere 4045T
➤ Max. Continuous BHP :	- 103 @ 2500 RPM ⁽⁵⁾
➤ Crankcase Oil:	- 14 quarts of SAE 10W40 ⁽³⁾
➤ Oil Press @ 800 RPM:	- 15 psi min.
➤ Safety Shutdowns:	- High water temperature & low oil pressure
➤ Grease Lubrication:	- No. 2 ⁽³⁾
➤ Fuel Capacity/Type:	- 88 gallons of No. 2 diesel
➤ Fuel Consumption:	- 5.5 gal/hr @ 2200 rpm
➤ Run Time:	- 16 hours @ 2200 RPM ⁽⁴⁾ 26 hours @ 1800 RPM
➤ Coolant:	- 16.5 gal. 50/50 water/antifreeze
➤ Number of Cyinders:	- Four
➤ Bore x Stroke:	- 4.19"x5.00"
➤ Fuel Filter:	- RE600021
➤ Oil Filter:	- RE59754
➤ Engine Air Filter:	- AT44377

Notes:

- ⁽¹⁾ Based on 1.0 specific gravity
- ⁽²⁾ Includes weight of trailer, pump, engine and empty fuel tank.
- ⁽³⁾ Midrange compromise. See John Deere manual.
- ⁽⁴⁾ Run time varies with engine operating speed.
- ⁽⁵⁾ **WARNING** – this is the rated speed for the ENGINE ONLY. The rated speed of the pump is only 2200 RPM.
- ⁽⁶⁾ Decreases with increasing flow rate.

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BAKER PUMPS, EITHER EXPRESS OR IMPLIED.