

PRODUCT DATA SHEET

December, 2000

ACCURATE INTERMODAL

GENERAL INFORMATION

This container is not to be used for free liquid storage.

WEIGHTS AND MEASURES

➤ Capacity:	25 yd ³
➤ Height:	6'-6"
➤ Width:	8'-0"
➤ Length:	19'-10½"
➤ Weight:	RT - 6415 lbs.; ML – 7615 lbs.

STRUCTURAL DESIGN

➤ Floor:	7-gauge steel plate
➤ Walls:	10-gauge steel plate
➤ Side Supports:	10-gauge steel, 3" deep x 10" wide
➤ Side Sills:	6" formed 10-gauge channel
➤ Floor Frame:	5" formed 10-gauge channel on 16" ctr's
➤ Door/Header:	Two horizontal and two vertical ¼" plate-formed channel frames, plus two 7-gauge vertical members. Door plate is 10-gauge steel. Three hinges at top. Hinge pins are stainless steel.
➤ Bulkhead:	10-gauge sheet steel with two vertical 2"x4"x¼" structural tubes welded to bulkhead sheet. Top horizontal tube 4"x4"x7 gauge min., A500, Grade B welded structural tube.
➤ Corners:	Eight standard ISO corner castings
➤ Truck Rails:	6"x2"x¼" structural tubing

APPURTENANCES

➤ Lid Options:	Open top, roll-tarp, metal lid (over/under)
➤ Liner Hooks:	"J" hooks
➤ Tarp Hooks:	(Tarped boxes only) Seven on each side of box. Three tarp straps on door.
➤ Wheels:	Four wheels 7¼" wide x 8½" dia. with swing-up/retractable locking mechanism

APPURTENANCES - cont

➤ Splashplates:	10-gauge steel plate on each end of container allowing 194" clear opening.
➤ Manifest Tube:	8" long, 1¼" pipe with cap and chain, driver's side, front
➤ Forklift Pockets:	81" centers, 14" wide min. and 4½" high min.
➤ Gaskets:	Door- pure neoprene SCE44/45 Lid- ISOLOSS LS-1525 & LS-1550
➤ Door Locks:	1-ratchet binder with chains each side 1-ratchet binder under floor with three grab hands on bottom of door.

SURFACE DETAILS

➤ Exterior Coating:	<u>Primer:</u> Carboline 890 Polyamide epoxy, color C703 <u>Paint:</u> Carboline 134HS Polyurethane
➤ Interior Lining:	Polyliners only, no coating
➤ Safety Paint:	None
➤ Equipment Number:	BKRU##### (Note: some containers may still have the former system of (Prefix)####(Suffix). Possible prefixes: I or IS, Possible suffixes: ML (metal lid) or RT (Roll Tarp)).
➤ Decals:	4-DCLB: Property of Baker Tanks... 2-DCLL: Liner Required for All Loads 2-DCLR01: Warning-Solids Only... 2-DCLW01: Warning – This Container... 4-DINVID: (single letter I.D.'s)
➤ Placard Mounts:	Four, one on both sides and both ends

TESTS/CERTIFICATIONS

➤ Tests Performed:	<ul style="list-style-type: none"> Water test after manufacture. Level I, II and III inspections thereafter. Top and bottom castings and corner post assembly hydraulically stress tested to three times rated capacity.
➤ Certification:	AARM930-90

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BAKER TANKS, EITHER EXPRESS OR IMPLIED.