

PRODUCT DATA SHEET

December, 2000

MAYFAB INTERMODAL

GENERAL INFORMATION

This container is not to be used for free liquid storage.

WEIGHTS AND MEASURES

➤ Capacity:	25 yd ³
➤ Height:	6'-4"
➤ Width :	8'-0"
➤ Length:	19'-10½"
➤ Tare Weight:	6080 lbs.
➤ Actual Vol:	664 cu. ft.
➤ Load Limit:	46,820 lbs.

STRUCTURAL DESIGN

➤ Floor:	7-gauge, one piece carbon steel
➤ Side Plate:	10-gauge, one piece, lower longitudinal edges radius formed inward
➤ Front Plate:	10-gauge, one piece
➤ Door Sheet:	10-gauge, one piece
➤ Crossbeams:	3" structural channels, 16" o.c.
➤ Bottom Rails:	6"x2"x¼" structural tubing
➤ Front/Rear Corner Posts:	6"x6"x3/16" structural tubing
➤ Corners:	Standard ISO corner fittings
➤ Front Rails:	6"x2"x3/16" structural tubing
➤ Header:	6"x3"x3/16" plate formed channel
➤ Top Rails:	4"x3"x3/16" structural tubing

FEATURES

➤ Lid Options:	Roll-tarp
➤ Tarp:	18 oz. Nylon reinforced canvas
➤ Tarp Bows:	1"x1"x16" gauge structural tubing
➤ Roll Pipe:	1½" schedule 5 galvanized pipe
➤ Crank Tube:	1.08" O.D. galvanized pipe

FEATURES - cont

➤ Wheels:	Retractable, 8" dia. x 7" long, at front and rear
➤ Fork Pockets:	12"x6"x¼" plate formed channels
➤ Door Latch:	Three independent ratchet binders and chains
➤ Hook:	1¼" plate, 36,000 psi min. yield strength
➤ Hook Plate:	¾" steel plate
➤ Door Gasket:	One piece EPDM extrusion with 12-gauge retainer clips
➤ Placard Mounts:	(4) aluminum holders riveted to 10-gauge sheets supported by 1x1x1/8 angle stand-offs
➤ Manifest Box:	(1)-aluminum box riveted to 10-gauge sheets supported by 1x1x1/8 angle stand-offs
➤ Splashguard:	10-gauge formed panels, both ends

SURFACE DETAILS

➤ Exterior Coating:	Primer: Carboline 890 Polyamide epoxy, color C703 Paint: Carboline 134HS Polyurethane
➤ Interior Lining:	Polyliners only, no coating
➤ Safety Paint:	None
➤ Equipment Number:	BKRU##### (Note: some containers may still have the former system of (Prefix)#####(Suffix). Possible prefixes: I or IS, Suffixes: RT (Roll Tarp)).
➤ Decals:	4-DCLB: Property of Baker Tanks... 2-DCLL: Liner Required for All Loads 2-DCLR01: Warning-Solids Only... 2-DCLW01: Warning – This Container... 4-DINVID: (single letter I.D.'s)

TESTS/CERTIFICATIONS

➤ Tests Performed:	Per AAR at manufacturer Baker Level inspections performed per QMS schedule.
➤ Certification:	AARM930-90

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BAKER TANKS, EITHER EXPRESS OR IMPLIED.